

# JVS-ND7916-HV

16CH H.265 2x SATA NVR



## Key Features

- Support 4K Output
- Support 4K IP Cameras Input
- Support Audio Input and Output;
- Two SATA Support, Up to 10TB Each;
- Support 485

## Description



Index	Description	Index	Description
①	Audio In	⑥	USB
②	Audio Out	⑦	Switch
③	VGA	⑧	RS-485
④	HDMI	⑨	Power
⑤	RJ45		

Model	JVS-ND7916-HV
Video and Audio	
IP Camera Input	16 Channel
Audio Input/ Output	1CH Input,1 Channel Output, RCA; Audio output support HDMI
Bandwidth I/O	320Mbps/160Mbps
Display	
Interface	1 HDMI, 1 VGA
Resolution	HDMI: 3840×2160, 1920×1080, 2560×1440, 1440×900, 1280×1024, 1280×720, 1024×768 VGA: 1920×1080, 1440×900, 1280×1024, 1280×720, 1024×768
Max Decoding	4K/ 5.0MP4.0MP/1080P/960P/720P 30fps
Multi-screen Display	1/4/5/6...13/14/15/16
OSD	Camera Name & Time, Recording, Alarm Detecting, Remote connection, Volume, Channel Number
Recording	
Compression	H.265/H.264
Record Mode	Manual, Schedule, MD
Video Detection and Alarm	
Trigger Events	Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer
Video Detection	Motion Detection, No Video Detection
Playback and Backup	
Sync Playback	1ch 4K, 2ch 5.0MP, 3ch 4.0MP, 4ch 3.0MP,4ch 1080P
Search Mode	Channel number / Recording type / Date
Playback Function	Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow, Step, Full Screen, Snap, Sound On/Off, Zoom
Backup Mode	FAT32 USB Device/Network
Network	
Interface	1 RJ-45 port (100/1000Mbps)
Network Function	TCP/IP, DHCP, UDP, SMTP, NTP
Smart Phone	iPhone, Android
Interoperability	ONVIF 2.4
Storage	
SATA	2 SATA interfaces
Capacity	up to 10TB
General	
Power Supply	DC 12V
Consumption	≤ 15 W (Without HDD)
Working Temperature	-10°C~ 55°C
Working Humidity	10 % ~ 90 %
Dimensions	360X45X264mm
Weight	≤ 2.0kg (Without HDD)